

Roblon Coated Lines

The coated lines from Roblon can be used for various applications, where high strength is required. The coated lines are ideal for use in harsh environments.

Key features

- Durable high-performance fibers and thermoplastic jacket material
- Non-corrosive materials
- The coated lines are available in various thicknesses from 3.5 mm up to 20 mm as standard - and in different materials depending on the properties required
- If other dimensions are required, please contact us
- The coated lines are either supplied loose in a cardboard box or on flange reels, depending on quantity



Roblon

Types of coated lines

Description/type	Colour	Dimension (mm) +/- 0.2 mm	Metre weight (g/m) +/- 10%	Min. breaking strength (kN)	Stiffness (kN)
Coated line, T2200	Yellow or black	Ø 3.50	11.14 g	3.8 kN	137
Coated line, T2200	Yellow or black	Ø 3.80	12.65 g	5.5 kN	190
Coated line, T2200	Yellow or black	Ø 4.00	14.47 g	7.1 kN	208
Coated line, T2200	Yellow or black	Ø 4.90	21.30 g	13.0 kN	435
Coated line, T2200	Yellow or black	Ø 5.25	24.75 g	13.1 kN	476
Coated line, T2200	Yellow or black	Ø 5.70	28.00 g	15.9 kN	584
Coated line, T2200	Yellow or black	Ø 6.00	32.26 g	21 kN	732
Coated line, T2200	Yellow or black	Ø 6.40	33.78 g	23.9 kN	848
Coated line, T2200	Yellow or black	Ø 7.20	44.55 g	34 kN	1006
Coated line/Rope, T2200	Orange	Ø 9.00	68.00 g	35 kN	TBA
Coated line/Rope, T2200	Orange	Ø 13.85	162.00 g	85 kN	TBA
Coated line/Rope, T2200	Orange	Ø 16.00	230.00 g	130 kN	TBA
Coated line/Rope, T2200	Orange	Ø 20.00	340.00 g	200 kN	TBA
Coated line, T200	Green	Ø 3.60	10.50 g	5.2 kN	125
Coated line, T200	Green	Ø 5.00	22.62 g	15 kN	450
Coated line, T200	Green	Ø 5.30	24.03 g	15 kN	450
Coated line, T200	Green	Ø 6.60	37.35 g	26 kN	880
Coated line, T200	Green	Ø 7.32	46.88 g	31 kN	1050
Coated line, Zylon	Orange	Ø 4.90	22.56 g	20 kN	835
Coated line, Zylon	Orange	Ø 6.90	43.43 g	46 kN	1770

28.04.2020



ISO9001 • ISO14001

001